

The IMPOP Series rotor—it's full featured for convenience, it's dependable and it's from a company you can trust, Toro.

IMPOP features include five interchangeable, color-coded nozzles to simplify installations. And, it includes both part- and full-circle arcs in one, so there's no need to carry additional products.

Most essential, it is well-built. Its heavy-duty construction ensures durability and continued function over time. And, IMPOP even works in dirty-water conditions with its straight flow-through path for positive action.



Toro IMPOP Series Rotary Sprinkler

Features

- Five interchangeable, color-coded nozzles for easy installation and identification
- Double-weighted splash arm to slow rotation and maximize radius
- Part- and full-circle arcs in one sprinkler
- Straight flow-through path ensures low pressure loss and positive action—even in very dirty water conditions
- Removable cap for easy servicing and debris removal
- Filter screen for debris resistance

Specifications

- Radius: 32'–45' (6,7m–13,7m)
- Flow rate: 1.5–8.4 GPM (5,6–31,7 LPM)
- Recommended operating pressure range: 25–60 psi (1,7–4,1 Bar)
- Optimum operating pressure: 50 psi (3,5 Bar)
- Combination ½" (13mm) or ¾" (20mm) female-threaded inlet
- Dimensions:
 - Cap diameter: 5" (12,7 cm)
 - Height: 9 9/16" (23,6cm)

Note: Specifications subject to change without notice.

For more information, contact your local Toro distributor.

IMPOP is a trademark of The Toro Company.

IMPOP Nozzle Performance Data

Pressure	Spacing	GPM	Nozzle	Pattern
30 psi	32'	1.5	Orange	▲ ¼
	33'	2.0	Red	■ ½
	35'	2.9	Black	◐ ½
	38'	3.8	Blue	◑ ¾
	39'	5.8	Green	● Full
40 psi	35'	1.8	Orange	▲ ¼
	37'	2.2	Red	■ ½
	39'	3.6	Black	◐ ½
	41'	4.2	Blue	◑ ¾
	43'	6.5	Green	● Full
50 psi	36'	2.3	Orange	▲ ¼
	40'	2.5	Red	■ ½
	41'	4.0	Black	◐ ½
	42'	5.1	Blue	◑ ¾
	45'	7.5	Green	● Full

Specifying Information

Model Number	Description
IMPOP	IMPOP Impact Sprinkler

