

RainSensor™ Series

residential, commercial

CONTROLLERS

For all residential applications, the wireless RainSensor automatically shuts off water when it rains. Coupled with the water saving features offered on Toro controllers, the RainSensor takes total water management a step further. For varying climates, RainSensor models include sensors for not only rain, but freeze as well.

Traditional wired model also available.



Receiver Wireless Transmitter



Plug-in transformer



Features

- Versatile mounting options (one-piece Quick-Clip[™] gutter bracket included – no special tools)
- Wired model includes 7,6m (25') of weather and UV resistant cable
- Compatible with almost any controller

Wireless Model Only

- Simple mounting with side/snap-on cover for added protection
- · Multi-functional receiver
 - Large LCD provides visual sensor status
 - Selectable water conservation modes (to delay resumption of irrigation)
 - Smart Bypass[™] allows for system override at any time and switches back on automatically
 - · Remaining battery life indicator
- · Signal strength indicator/scale
- Selectable rain shut-off indexes at 3, 6, 13, and 20mm (1/8", 1/4", 1/2", and 3/4") of rain
- · Extended 3-year warranty

Specifications (Wireless Model)

- Operating temperature: -28.9°C to 48.9°C (-20°F to 120°F)
- Housing material: Weather and UV-resistant engineered polymer
- FCC, IC, ACA, UL, CUL, CE and C-Tick approved

Transmitter

- Transmitting range: Up to 152m (500')
- Sensor: maintenance-free hygroscopic disks; adjustable rain sensitivity 3-20mm (1/8" to 3/4")
- Power source: 2 lithium coin cells (CR2032-3V)

Receiver

- Factory set to Normally Closed (N.C.); can be set to Normally Open (N.O.), 3A @ 24 V ac
- Power: 22–28 V ac/VDC, 100mA

Options

Digital Freeze Sensor

- Reduces vegetation damage and accidents
- Fully integrated into the wireless unit
- Current outdoor temperature displayed on LCD
- Adjustable freeze shutoff point (1,7-7,2°C or 35-45°F) an industry first



Wireless Transmitter

Specifying Information	
Model	Description
TRS	Toro Wired RainSensor
TWRS	Toro Wireless RainSensor
TWRS-I	Toro Wireless Rain Sensor (International Version)
TWRFS	Toro Wireless Rain/Freeze Sensor
TWRFS-I	Toro Wireless Rain/Freeze Sensor (International Version)

TORO. Count on it.

Worldwide Headquarters The Toro Company 8111 Lyndale Avenue South Bloomington, MN 55420 Phone: 952-888-8801 Fax: 952-887-7265 www.toro.com

GB Form Number: 200-2802 ©2005 The Toro Company – All Rights Reserved.